



US006284976B1

(12) **United States Patent**
Pulido et al.

(10) **Patent No.:** **US 6,284,976 B1**
(45) **Date of Patent:** **Sep. 4, 2001**

(54) **CABLE CLOSURE INJECTION SEALED
WITH ORGANO BORANE AMINE
COMPLEX**

(75) **Inventors:** **Jacqueline J. Pulido; Kenneth D. Rebers; Thomas S. Croft**, all of Austin, TX (US); **Alan J. Oshinski**, Kingsport, TN (US); **Kwang H. Chu; Daniel G. Lee**, both of Austin, TX (US); **Russell P. Smith**, Georgetown, TX (US)

(73) **Assignee:** **3M Innovative Properties Company**, St. Paul, MN (US)

(*) **Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

2,967,795	1/1961	Bollmeier et al.	174/84 R
3,215,761	11/1965	Gelpey	264/139
3,290,194	12/1966	Gillemot	156/48
3,427,393	2/1969	Masterson	174/23 R
3,836,694	9/1974	Kapell	174/22
3,903,595	9/1975	Takada et al.	29/628
4,287,386	9/1981	Scahill et al.	174/76
4,332,975	6/1982	Dienes	174/76
4,387,268	6/1983	Morel et al.	174/92
4,444,996	4/1984	Robertson	174/74 A
4,492,816 *	1/1985	Morel et al.	174/92
4,607,469	8/1986	Harrison	52/220
4,822,434	4/1989	Sawaki et al.	156/48
5,124,507	6/1992	Dehling	174/92
5,258,578	11/1993	Smith et al.	174/93
5,302,779	4/1994	Morel et al.	174/92
5,396,033	3/1995	Piriz et al.	174/94 R
5,539,070	7/1996	Zharov et al.	526/198
5,886,300 *	3/1999	Strickler	174/92

(21) **Appl. No.:** **09/569,202**

* cited by examiner

(22) **Filed:** **May 11, 2000**

Related U.S. Application Data

(62) Division of application No. 09/267,445, filed on Mar. 12, 1999, now Pat. No. 6,064,006, which is a continuation of application No. 08/784,485, filed on Jan. 17, 1997, now Pat. No. 5,912,433.

(51) **Int. Cl.⁷** **H02G 15/08**

(52) **U.S. Cl.** **174/77 R; 174/93; 174/74 R; 174/92**

(58) **Field of Search** **174/77 R, 93, 174/92, 74 R, 84 R, 74 A**

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,792,441 5/1957 Platow 174/23 R

Primary Examiner—Dean A. Reichard

Assistant Examiner—William H. Mayo, III

(74) *Attorney, Agent, or Firm*—Darla P. Fonseca

(57)

ABSTRACT

A cable splice closure includes a closure body having mating surfaces sealed together. An end seal in the closure has an opening for receiving a cable. The end seal is sealed to the closure body by an adhesive bond. An adhesive injection port in the end seal. The port is provided to communicate an adhesive injected into the end seal to bond surfaces of the end seal and the cable to be received, into a sealed unit. The adhesive is a low surface energy adhesive based on acrylic monomers with organoborane are complexes.

12 Claims, 10 Drawing Sheets

